Docket No: 19264.0007II2
Title   System and Method for Generating a
           Genetically Engineered Configuration for at
           Least One Antenna and/or a Frequency
           Selective Surface
Atty'   JPM

FIG.1

A_1

A_3

A_2

A_0

w_1

w_2

w_3

w_4

FIG.2

Docket No.: 19264.0007U2
Title: System and Method for Generating a
Genetically Engineered Configuration for at
Least One Antenna and/or a Frequency
Selective Surface
Atty: JPM

3/43

FIG.3A

a	b	c	d	e	f
0.255	0.0	0.0	0.255	0.3726	0.6714
0.255	0.0	0.0	0.255	0.1146	0.2232
0.255	0.0	0.0	0.255	0.6306	0.2232
0.370	-0.642	0.642	0.370	0.6356	-0.0061

FIG.3

Docket No: 19264.0007U2
Title: System and Method for Generating a
Genetically Engineered Configuration for at
Least One Antenna and/or a Frequency
Selective Surface
Atty: JPM

4/43

FIG.4A

a	b	c	d	e	f
0.195	-0.488	0.344	0.443	0.4431	0.2452
0.462	0.414	-0.252	0.361	0.2511	0.5692
-0.058	-0.07	0.453	-0.111	0.5976	0.0969
-0.035	0.07	-0.469	-0.022	0.4884	0.5069
-0.637	0.0	0.0	0.501	0.8562	0.2513

FIG.4

W_3

W_2

W_4

W_1

W_5

FIG.5

LOAD 1 AT
WIRE #11

LOAD 2 AT
WIRE #18

h

L

FIG.6

Docket No: 19264.0007U2
Title   System and Method for Generating a
        Genetically Engineered Configuration for at
        Least One Antenna and/or a Frequency
        Selective Surface
Any   JPM

6/43

├─────────────────── 12 cm ───────────────────┤

FIG.7

1.22 cm

├──────── 5.5 cm ────────┤

FIG.8

NEC4
(SUBROUTINE)

920

GA
(MAIN PROGRAM)

900

FIG.9

FRACTAL
(SUBROUTINE)

910

1000

FIG.10

LENGTH OF ANTENNA = 12 cm

LOAD LOCATIONS : LOAD1 ELEMENT 21   L1 = 15.81250 nH   C1 = 0.4849 pF
                LOAD2 ELEMENT 06   L2 = 17.98438 nH   C2 = 0.7996 pF

FREQUENCY	VSWR
1225 MHz	1.3383
1575 MHz	1.2872

FIG.11

"LOADED" GENE/CODE

LENGTH OF ANTENNA = 11.5 cm
LOAD LOCATIONS : LOAD1 ELEMENT 21   L1 = 15.53125 nH   C1 = 0.5376 pF
                 LOAD2 ELEMENT 06   L2 = 17.95312 nH   C2 = 0.8453 pF

FREQUENCY	VSWR
1225 MHz	1.2649
1575 MHz	1.2266

FIG.12

Docket No: 19264-0007U2
Title: System and Method for Generating a Genetically Engineered Configuration for at Least One Antenna and/or a Frequency Selective Surface
Atty: JPM

10/43

LENGTH OF ANTENNA = 11.0 cm
LOAD LOCATIONS : LOAD1 ELEMENT 05   L1 = 17.26562 nH   C1 = 0.4708 pF
LOAD2 ELEMENT 04   L2 = 17.89062 nH   C2 = 0.9648 pF

FREQUENCY	VSWR
1225 MHz	1.0738
1575 MHz	1.3285

FIG.13

LENGTH OF ANTENNA = 10.5 cm
LOAD LOCATIONS : LOAD1 ELEMENT 22 $L1$ = 13.93750 nH $C1$ = 0.6414 pF
                LOAD2 ELEMENT 04 $L2$ = 18.92188 nH $C2$ = 0.9050 pF

| FREQUENCY	VSWR
1225 MHz	1.1249
1575 MHz	1.1205

FIG.14

"DUAL LC" LOADED DIPOLE

LENGTH OF ANTENNA = 10.0 cm
LOAD LOCATIONS : LOAD1 ELEMENT 25   L1 = 15.98438 nH   C1 = 0.5746 pF
                LOAD2 ELEMENT 23   L2 = 13.39062 nH   C2 = 0.6712 pF

FREQUENCY	VSWR
1225 MHz	1.1884
1575 MHz	1.1103

FIG.15

Title: System and Method for Generating a
Genetically Engineered Configuration for at
Least One Antenna and/or a Frequency
Selective Surface

Any JPM

13/43

LENGTH OF ANTENNA = 9.5 cm
LOAD LOCATIONS : LOAD1 ELEMENT 22 $L1 = 13.48438$ nH $C1 = 0.6941$ pF
LOAD2 ELEMENT 25 $L2 = 12.09375$ nH $C2 = 0.1509$ pF

FREQUENCY	VSWR
1225 MHz	1.0386
1575 MHz	1.1186

FIG.16

Title System and Method for Generating a
Genetically Engineered Configuration for at
Least One Antenna and/or a Frequency
S:Medcuse Surgace
Atty JPM

14/43

LENGTH OF ANTENNA = 9.0 cm
LOAD LOCATIONS : LOAD1 ELEMENT 25   L1 = 12.04688 nH   C1 = 0.3302 pF
LOAD2 ELEMENT 05   L2 = 15.43750 nH   C2 = 0.6642 pF

FREQUENCY	VSWR
1225 MHz	1.0392
1575 MHz	1.1430

FIG.17

LENGTH OF ANTENNA = 8.5 cm
LOAD LOCATIONS : LOAD1 ELEMENT 25 $L1$ = 18.79688 nH $C1$ = 0.5570 pF
                LOAD2 ELEMENT 09 $L2$ = 15.43750 nH $C2$ = 0.6853 pF

FREQUENCY	VSWR
1225 MHz	1.1235
1575 MHz	1.0224

FIG.18

CONFIG"GE1/21004

LENGTH OF ANTENNA = 8.0 cm
LOAD LOCATIONS : LOAD1 ELEMENT 04   L1 = 13.42188 nH   C1 = 0.1457 pF
                LOAD2 ELEMENT 04   L2 = 16.15625 nH   C2 = 0.7644 pF

FREQUENCY	VSWR
1225 MHz	1.1432
1575 MHz	1.0470

FIG.19

LENGTH OF ANTENNA = 7.5 cm
LOAD LOCATIONS : LOAD1 ELEMENT 04   L1 = 13.50000 nH   C1 = 0.3671 pF
                LOAD2 ELEMENT 25   L2 = 18.35938 nH   C2 = 0.8910 pF

FREQUENCY   VSWR
1225 MHz   1.0453
1575 MHz   1.1628

FIG.20

LENGTH OF ANTENNA = 7.0 cm
LOAD LOCATIONS : LOAD1 ELEMENT 23   L1 = 17.95312 nH   C1 = 0.8119 pF
LOAD2 ELEMENT 19   L2 = 19.50000 nH   C2 = 0.1017 pF

FREQUENCY	VSWR
1225 MHz	1.3338
1575 MHz	1.1024

FIG.21

COST "D" GEN/GEODE

LENGTH OF ANTENNA = 6.5 cm
LOAD LOCATIONS : LOAD1 ELEMENT 22   L1 = 16.10938 nH   C1 = 0.8962 pF
                LOAD2 ELEMENT 12   L2 = 13.01562 nH   C2 = 0.2107 pF

FREQUENCY	VSWR
1225 MHz	1.6677
1575 MHz	1.4982

FIG.22

LENGTH OF ANTENNA = 6.0 cm

LOAD LOCATIONS : LOAD1 ELEMENT 22   L1 = 16.35938 nH   C1 = 0.8962 pF

                    LOAD2 ELEMENT 09   L2 = 16.12500 nH   C2 = 0.3214 pF

FREQUENCY	VSWR
1225 MHz	1.6956
1575 MHz	1.4979

FIG.23

BENT "Z0" CONDUCTOR

LENGTH OF ANTENNA = 5.5 cm
LOAD LOCATIONS : LOAD1 ELEMENT 22   L1 = 15.86914 nH   C1 = 0.9308 pF
                LOAD2 ELEMENT 16   L2 = 12.51172 nH   C2 = 0.5371 pF

FREQUENCY	VSWR
1225 MHz	1.9413
1575 MHz	1.7861

FIG.24

VSWR
3.8461
147.6503

FREQUENCY
1225
1575

FIG.25

VSWR
7.7811
34.0082

FREQUENCY
1225
1575

FIG.26

FREQUENCY	VSWR
1225	6.2696
1575	37.7545

FIG.27

FREQUENCY	VSWR
1225	5.6053
1575	34.3092

FIG.28

FREQUENCY	VSWR
1225	5.5536
1575	34.3092

FIG.29

FREQUENCY	VSWR
1225	3.9846
1575	30.16798

FIG.30

VSWR	FREQUENCY
5.0477	1225
4.1741	1575

FIG.31

Docket No: 19264.0007U2
Title: System and Method for Generating a
Genetically Engineered Configuration for at
Least One Antenna and/or a Frequency
Selective Surface
Atty: JPM

29/43

FREQUENCY	VSWR
1225	1.8738
1575	9.9798

FIG.32

FREQUENCY	VSWR
1225	1.9631
1575	1.8005

FIG.33

FREQUENCY VSWR
1225 1.9578
1575 1.7579

FIG.34

VSWR
1.9486
1.7735

FREQUENCY
1225
1575

FIG.35

Docket No   19264 0007U2
Title   System and Method for Generating a
                   Genetically Engineered Configuration for at
                   Least One Antenna and/or a Frequency
Atty   SSlective Surgace
                   JPM

33/43

FREQUENCY	VSWR
1225	1.9453
1575	1.7947

FIG.36

FREQUENCY	VSWR
1225	1.9415
1575	1.7904

FIG.37

Title System and Method for Generating a
Genetically Engineered Configuration for at
Least One Antenna and/or a Frequency
Selective Surface
Any JPM

35/43

VSWR
1.9413
1.7861

FREQUENCY
1225
1575

FIG.38

FIG.39

FIG.40

FIG.41

FIG.42

SOURCE

FIG.43

FREQUENCY (MHz)	VSWR	ZIN	GAIN
1225.0	1.579067	(32.47140,−6.125150)	2.030
1575.0	1.262626	(39.63660,−0.9270540)	2.610

FIG.44

Title   System and Method for Generating a
         Genetically Engineered Configuration for at
         Least One Antenna and or a Frequency
         Sillective Surface
Atty   JPM

42/43

FIG.45

Title   System and Method for Generating a
Genetically Engineered Configuration for at
Least One Antenna and/or a Frequency
Selective Surface

Aty   JPM

FIG.46

FIG.47